









Pearl Oak VE75PAEO NU OII Sandbar VE75SANH









Benefits

Finish MAPLE, HICKORY, WALNUT - GlazeTek® - 10x more

durable than UV Oil

3x more durable than UV Poly

OAK- NuOil® - No recoat at time of install Best stain protection & color retention

Completely VOC free

100% Renewable w/Warranty intact

Structure MG2 - 2 Guaranteed sanding's

Highest possible stability

w/ slice cut faces

Guaranteed Third Party Certification

Truecore - FSC certified Highest Green Certification Lifetime Structural Guarantee

Clean Air CARB II - Surpasses standard by over 50%

Features

Length: Random up to 6'2"

Width: 7.5"

Thickness: 1/2" thick

2 mm slice-cut face Truecore Centerply

Surface Texture: Lightly Wire Brushed

Finish: NuOil® (Oak)

TrueMark GlazeTek (Maple, Hickory,

Walnut)

Usage: Residential, EN31, EN 32

Edge Detail: Handcrafted Microbevel

Warranty: Lifetime Residential finish

Lifetime Residential structural

3 year commercial finish 10 year commercial structural



Color, Graining & Natural Changes

Wood is a natural product that features distinct color and graining. Each board is unique in its characteristics and will vary from piece to piece. The floor represents the natural visual characteristics of wood. Each board can vary from a clean to rustic visual and contain large to small filled knots, sap wood, small to large filled splits and a high contrast within the natural and lighter stained visuals. These subtleties may become more distinct over time due to exposure to direct sunlight. Occasional rearranging of furniture and rugs will help reduce the potential effects of the sun.

Note: This sample may not be representative of your entire installed floor, for your reference and the latest updated information, please refer to www.hallmarkfloors.com to see our online room scenes and project galleries.

Maintenance

See Maintenance and Warranty Guide Carb II Compliant

Installation



Nail Down



Glue Down



Float



Over Radiant Heat [EXCLUDING HICKORY]

Installs over: concrete, wood, vinyl floors and radiant heat systems. Above, on or below grade. See complete installation instructions.

Trim Options

Stair Nose Reducer

T-molding Quarter Round

Threshold







