



RECOMMENDED AREAS OF USE

With regard to the durability of the bisque and glaze, this material is suitable for:

- All vertical applications - residential and commercial
- All interior wall, countertop and floor applications
- Fireplace surround, hearth and firebox
- Light commercial flooring applications
- All exterior wall applications including building facades, swimming pools, fountains and outdoor kitchens, including regions that experience extreme weather conditions subject to the method of installation



BRICKWORKS

2 1/2" x 9"

www.mycreativetile.com/product-category/brands/cepac-tile/brickworks-collection/

INSTALLATION AND MAINTENANCE

- Please refer to the TCNA handbook for installation method <http://www.tcnatile.com/>
- Always inspect material prior to installation, for color, shade, size, mounting and any other deciding factors as installed material cannot be accepted for return or credit. Use signifies acceptance.
- Recommended Grout Joint: 3/16" or greater
- Material can be cleaned with any mild nonabrasive household cleaning product due to the chemical resistant nature of the glaze.

PROFILE

Available in two shades, Polar and Earth, Brickworks creates a practical yet visually pleasing contemporary look to interior and exterior facades. With its' rich textured surface and varied glazes, this material will add organic character to all your projects.

Coordinating Trim 2 1/2" x 9":

Short side Surface Bullnose
Long side Surface Bullnose
Right & Left Side Down Angles

Creative Tile
7030 N Harrison Ave
Fresno, CA 93650
(559) 436-8453

www.mycreativetile.com
info@mycreativetile.com

Where Excellence in Quality & Service Unite!

TECHNICAL DATA

- Japanese Stoneware
- Chemical Resistant
- Due to the handmade nature of this product, there is a wide variation in the glazing and texture from piece to piece.
- Water absorbency
 - Bisque less than 1%
 - Glazed surface 0%
- TCNA - MOH's Scale Rating 7
- TCNA - DCOF - BR-291: Avg. Rating: 0.34
- TCNA - DCOF - BR-292: Avg. Rating: 0.24
- Loose pieces - 6 pieces = 1 sq. ft. / 60 pieces = 10 sq. ft. per box
- Weight - 4.75 lbs. per sq. ft. / 48 lbs. per box
- Thickness - 1/2"
- Pre-consumer recycled content - 34%
- Variations of shade are inherent characteristics of all kiln fired products. To ensure satisfaction, please visually inspect all merchandise prior to installation, as use signifies acceptance.
- We will endeavor to resolve any issues that may arise with material purchased prior to installation.