

cove

PRODUCT SHEET

CONCRETE LOOK

THICKNESS ∇ 9 mm

FINISH MATTE

 V2 SLIGHT VARIATION


  Compliant with standards ANSI A137.1-2012

Inspired by chalk manually spread by artisans, our Cove Collection creates spaces of great material expressiveness and artisanal beauty. Thin scratches and delicate reliefs on the surface, combined with neutral tones, give spaces a contemporary, handcrafted look suitable for every kind of application.


COLORS



SIZES



23⁵/₈" x 47¹/₄" - 60x120 cm



11³/₄" x 23⁵/₈" - 30x60 cm



HEXAGON
9⁷/₈" x 8¹/₂" - 25x21.6 cm



COVE ARTISAN COLD
7⁷/₈" x 7⁷/₈"
20x20 cm



COVE DECO COLD
7⁷/₈" x 7⁷/₈"
20x20 cm



COVE ARTISAN WARM
7⁷/₈" x 7⁷/₈"
20x20 cm



COVE DECO WARM
7⁷/₈" x 7⁷/₈"
20x20 cm


MOSAICS & DECORS




COVE BREEZE MOSAIC
11³/₄" x 11³/₄" - 30x30 cm
(Mosaic 2"x2")



COVE LINEN MOSAIC
11³/₄" x 11³/₄" - 30x30 cm
(Mosaic 2"x2")



COVE PEBBLE MOSAIC
11³/₄" x 11³/₄" - 30x30 cm
(Mosaic 2"x2")



COVE COAST MOSAIC
11³/₄" x 11³/₄" - 30x30 cm
(Mosaic 2"x2")



COVE STORM MOSAIC
11³/₄" x 11³/₄" - 30x30 cm
(Mosaic 2"x2")

MOOD



COVE BREEZE APEX MOSAIC
11"x11" - 28x28 cm
(Mosaic 1.8"x5.5")



COVE LINEN APEX MOSAIC
11"x11" - 28x28 cm
(Mosaic 1.8"x5.5")



COVE PEBBLE APEX MOSAIC
11"x11" - 28x28 cm
(Mosaic 1.8"x5.5")



COVE COAST APEX MOSAIC
11"x11" - 28x28 cm
(Mosaic 1.8"x5.5")



COVE STORM APEX MOSAIC
11"x11" - 28x28 cm
(Mosaic 1.8"x5.5")



COVE BREEZE DART MOSAIC
11³/₄" x 11³/₄" - 30x30 cm
(Mosaic 1.3"x4.2")



COVE LINEN DART MOSAIC
11³/₄" x 11³/₄" - 30x30 cm
(Mosaic 1.3"x4.2")



COVE PEBBLE DART MOSAIC
11³/₄" x 11³/₄" - 30x30 cm
(Mosaic 1.3"x4.2")




COVE COAST DART MOSAIC 11³/₄" x 11³/₄"
30x30 cm
(Mosaic 1.3"x4.2")




COVE STORM DART MOSAIC
11³/₄" x 11³/₄" - 30x30 cm
(Mosaic 1.3"x4.2")

COORDINATING TRIMS



Bullnose
3" x 24" - 7.2x60 cm



Cove base
6" x 12" - 15x30 cm - ∇ 8.5mm

Be sure to bring this to your local tile dealer or distributor as you discuss your design.

COLORED BODY PORCELAIN TILE



Compliant with standards ANSI A137.1-2012

SIZE - THICKNESS

11 3/4" x 23 5/8" - 30 x 60 cm
 23 5/8" x 47 1/4" - 60 x 120 cm
 9 7/8" x 8 1/2" - 25 x 21.6 cm
 7 7/8" x 7 7/8" - 20 x 20 cm

± 9 mm

FINISH

MATTE



V2

SLIGHT VARIATION

Clearly distinguishable differences in texture and/or pattern within similar colors.

FIELD TILES - Available in all colors

Commercial size (in)	Nominal size (in)	Thickness (mm)	Finish	Rectified Edge
12" x 24"	11 3/4" x 23 5/8"	9 mm	Matte	-
24" x 48"	23 5/8" x 47 1/4"	9 mm	Matte	Yes
10" x 8.5"	9 7/8" x 8 1/2"	9 mm	Matte	-
8" x 8"	7 7/8" x 7 7/8"	9 mm	Matte	-

MOSAICS AND COORDINATING TRIMS - Available in all colors

Commercial size (in)	Nominal size (in)	Thickness (mm)	Finish
Mosaic 2" x 2"	11 3/4" x 11 3/4"	9 mm	Matte
Dart Mosaic 1.3" x 4.2"	11 3/4" x 11 3/4"	9 mm	Matte
Apex Mosaic 1.8" x 5.5"	11" x 11"	9 mm	Matte
Bullnose 3" x 24"	2 7/8" x 23 5/8"	9 mm	Matte
Cove Base 6" x 12"	5 7/8" x 11 3/4"	8.5 mm (*)	Matte

Please refer to caliber chart for work sizes. Close joints are not recommended.

(*): Cove Base thickness is 7mm on flat part.

PERFORMANCE & FEATURES

	PROPERTY	ASTM TEST METHOD	Porcelain Tile Specification					
			Calibrated		Rectified			
			Minimum	Maximum	Minimum	Maximum		
REGULARITY CHARACTERISTICS	Nominal Size	ASTM C499	-3.00%	3.00%	-3.00%	2.00%	Compliant	
			Caliber Range (Variation from average facial dimension of sample)	-0.50% or -0.08 in (-2.0 mm) (*)	0.50% or 0.08 in (2.0 mm) (*)	-0.25% or -0.03 in (-0.8 mm) (*)	0.25% or 0.03 in (0.8 mm) (*)	Compliant
			Thickness (1)	N/A	Range: 0.40 in (1.02 mm)	N/A	Range: 0.40 in (1.02 mm)	Compliant
	Wedging	ASTM C502	-0.50% or -0.08 in (-2.0 mm) (*)	0.50% or 0.08 in (2.0 mm) (*)	-0.25% or -0.03 in (-0.8 mm) (*)	0.25% or 0.03 in (0.8 mm) (*)	Compliant	
	Warpage Edge	ASTM C485	-0.75% or -0.09 in (-2.3 mm) (*)	0.75% or 0.09 in (2.3 mm) (*)	-0.40% or -0.05 in (-1.3 mm)(2) or -1.8 mm(3) (*)	0.40% or 0.05 in (1.3 mm)(2) or 1.8 mm(3) (*)	Compliant	
Warpage Diagonal	-0.50% or -0.08 in (-2.0 mm) (*)		0.50% or 0.08 in (2.0 mm) (*)	-0.40% or -0.07 in (-1.8 mm) (*)	0.40% or 0.07 in (1.8 mm) (*)	Compliant		
All Porcelain Tiles								
STRUCTURAL CHARACTERISTICS	Water Absorption	ASTM C373	≤ 0.5%			≤ 0.5%		
BULK MECHANICAL CHARACTERISTICS	Breaking Strength	ASTM C648	Average ≥ 250 lbf. (1.11 kN) Individual ≥ 225 lbf. (1.00 kN)			≥ 350 lbf. avg		
PHYSICAL PROPERTIES	Bond Strength	ASTM C482	≥ 50 psi (0.34 Mpa)			≥ 100 psi		
THERMAL AND IGROMETRIC CHARACTERISTICS	Resistance to Freeze/Thaw Cycling	ASTM C1026	As Reported			Resistant		
CHEMICAL CHARACTERISTICS	Chemical Resistance	ASTM C650	As Reported			Unaffected		
	Stain Resistance	ASTM C1378	As Reported			Unaffected		
SAFETY CHARACTERISTICS	Dynamic coefficient of friction	DCOF	Requires a minimum value of 0.42 for commercial areas that are likely to be wet			> 0.42 Wet		

(*) Whichever is less

(1) May not apply to textured surfaces or tiles with uneven back patterns.

(2) Whichever is less, for tiles up to 24"x24" (610 mm x 610 mm).

(3) Applies to tiles larger than 24"x24" (610 mm x 610 mm).

The Health Product Declaration® logo is a registered trademark of HPD Collaborative.

