

liberty

PRODUCT SHEET

MARBLE LOOK

THICKNESS ∇ 9 mm

FINISH MATTE

 V2 SLIGHT VARIATION



Compliant with standards ANSI A137.1-2012

Marble has always been one of the most popular materials in the farmhouse trend, but this collection exudes an unmatched brilliance. Illuminate your home or working space with one of the four distinguished shades of sophistication. Available in highly refined shades, a complete range of sizes, and matching glossy wall tiles.

SIZES



11³/₄"x23⁵/₈" - 30x60 cm


COLORS



LIBERTY CALACATTA CENTENNIAL



LIBERTY NEW ENGLAND




LIBERTY MONUMENT CREAM



LIBERTY FRANKLIN GRAY

MOSAICS & DECORS



LIBERTY CALACATTA CENTENNIAL MOSAIC
11³/₄"x11³/₄" - 30x30 cm
(Mosaic 2"x2")



LIBERTY NEW ENGLAND MOSAIC
11³/₄"x11³/₄" - 30x30 cm
(Mosaic 2"x2")



LIBERTY MONUMENT CREAM MOSAIC
11³/₄"x11³/₄" - 30x30 cm
(Mosaic 2"x2")




LIBERTY FRANKLIN GRAY MOSAIC
11³/₄"x11³/₄" - 30x30 cm
(Mosaic 2"x2")

MOOD



LIBERTY CALACATTA CENTENNIAL BRICK MOSAIC
11³/₄"x11³/₄" - 30x30 cm
(Mosaic 2"x4")



LIBERTY NEW ENGLAND BRICK MOSAIC
11³/₄"x11³/₄" - 30x30 cm
(Mosaic 2"x4")



LIBERTY MONUMENT CREAM BRICK MOSAIC
11³/₄"x11³/₄" - 30x30 cm
(Mosaic 2"x4")



LIBERTY FRANKLIN GRAY BRICK MOSAIC
11³/₄"x11³/₄" - 30x30 cm
(Mosaic 2"x4")



LIBERTY CALACATTA CENTENNIAL CHEVRON MOSAIC
7¹/₂"x12³/₈" - 19x31.5 cm
(Mosaic 2"x5")



LIBERTY FRANKLIN GRAY CHEVRON MOSAIC
7¹/₂"x12³/₈" - 19x31.5 cm
(Mosaic 2"x5")



LIBERTY FRANKLIN GRAY HONEYCOMB MOSAIC
9¹/₂"x11⁷/₈" - 24x30 cm
(Mosaic 3.5"x3")




LIBERTY MONUMENT CREAM HONEYCOMB MOSAIC
9¹/₂"x11⁷/₈" - 24x30 cm
(Mosaic 3.5"x3")

COORDINATING TRIMS



Bullnose
3"x 24" - 7.2x60 cm



Cove base
6"x12" - 15x30 cm - ∇ 8.5mm

Be sure to bring this to your local tile dealer or distributor as you discuss your design.

COLORED BODY PORCELAIN TILE



Compliant with standards ANSI A137.1-2012

SIZE - THICKNESS

11^{3/4}" x 23^{5/8}" - 30x60 cm ∇ 9 mm

FINISH

MATTE



SLIGHT VARIATION

Clearly distinguishable differences in texture and/or pattern within similar colors.

FIELD TILES - Available in all colors

Commercial size (in)	Nominal size (in)	Thickness (mm)	Finish
12"x24"	11 3/4" x 23 5/8"	9 mm	Matte

MOSAICS AND COORDINATING TRIMS - Available in all colors

Commercial size (in)	Nominal size (in)	Thickness (mm)	Finish
Mosaic 2"x2"	11 3/4" x 11 3/4"	9 mm	Matte
Brick Mosaic 2"x4"	11 3/4" x 11 3/4"	9 mm	Matte
Chevron Mosaic 2"x5"	7 1/2" x 12 3/8"	9 mm	Matte
Bullnose 3"x24"	2 7/8" x 23 5/8"	9 mm	Matte
Cove Base 6"x12"	5 7/8" x 11 3/4"	8.5 mm (*)	Matte

Please refer to caliber chart for work sizes.
Close joints are not recommended.
(*): Cove Base thickness is 7 mm on flat top part.

PERFORMANCE & FEATURES

PROPERTY	ASTM TEST METHOD	Porcelain Tile Specification				LIBERTY	
		Calibrated		Rectified			
		Minimum	Maximum	Minimum	Maximum		
REGULARITY CHARACTERISTICS	 Nominal Size Caliber Range (Variation from average facial dimension of sample) Thickness ⁽¹⁾	ASTM C499	-3.00%	3.00%	-3.00%	2.00%	Compliant
			-0.50% or -0.08 in (-2.0 mm) (*)	0.50% or 0.08 in (2.0 mm) (*)	-0.25% or -0.03 in (-0.8 mm) (*)	0.25% or 0.03 in (0.8 mm) (*)	Compliant
			N/A	Range: 0.40 in (1.02 mm)	N/A	Range: 0.40 in (1.02 mm)	Compliant
	 Wedging Warpage Edge Warpage Diagonal	ASTM C502	-0.50% or -0.08 in (-2.0 mm) (*)	0.50% or 0.08 in (2.0 mm) (*)	-0.25% or -0.03 in (-0.8 mm) (*)	0.25% or 0.03 in (0.8 mm) (*)	Compliant
			ASTM C485	-0.75% or -0.09 in (-2.3 mm) (*)	0.75% or 0.09 in (2.3 mm) (*)	-0.40% or -0.05 in (-1.3 mm) ⁽²⁾ or -1.8 mm ⁽³⁾ (*)	0.40% or 0.05 in (1.3 mm) ⁽²⁾ or 1.8 mm ⁽³⁾ (*)
		All Porcelain Tiles					
STRUCTURAL CHARACTERISTICS	 Water Absorption	ASTM C373	≤ 0.5%		≤ 0.5%		
BULK MECHANICAL CHARACTERISTICS	 Breaking Strength	ASTM C648	Average ≥ 250 lbf. (1.11 kN) Individual ≥ 225 lbf. (1.00 kN)		≥ 350 lbf. avg		
PHYSICAL PROPERTIES	 Bond Strength	ASTM C482	≥ 50 psi (0.34 Mpa)		≥ 100 psi		
THERMAL AND IGROMETRIC CHARACTERISTICS	 Resistance to Freeze/ Thaw Cycling	ASTM C1026	As Reported		Resistant		
CHEMICAL CHARACTERISTICS	 Chemical Resistance	ASTM C650	As Reported		Unaffected		
	 Stain Resistance	ASTM C1378	As Reported		Unaffected		
SAFETY CHARACTERISTICS	 Dynamic coefficient of friction	DCOF	Requires a minimum value of 0.42 for commercial areas that are likely to be wet		> 0.42 Wet		

(*) Whichever is less
(1) May not apply to textured surfaces or tiles with uneven back patterns.
(2) Whichever is less, for tiles up to 24"x24" (610 mm x 610 mm).
(3) Applies to tiles larger than 24"x24" (610 mm x 610 mm).

The Health Product Declaration® logo is a registered trademark of HPD Collaborative.

