

shore

PRODUCT SHEET

STONE LOOK

THICKNESS ∇ 9 mm

FINISH MATTE



V3 MODERATE VARIATION



Compliant with standards ANSI A137.1-2012

The typical curved veins of the cross-cut travertine are masterfully embodied in our Shore Collection. The natural essence of this renowned stone is enhanced by the visible but delicate veins on the surface and the wide selection of neutral shades, making this collection extremely versatile and consistent with today's coastal trend.

SIZES



23^{5/8}"x47^{1/4}" - 60x120 cm



11^{3/4}"x23^{5/8}" - 30x60 cm

COLORS



SHORE CREST



SHORE SAND



SHORE MARINE

MOSAICS & DECORS



SHORE CREST MOSAIC

11^{3/4}"x11^{3/4}" - 30x30 cm
(Mosaic 2"x2")



SHORE SAND MOSAIC

11^{3/4}"x11^{3/4}" - 30x30 cm
(Mosaic 2"x2")



SHORE MARINE MOSAIC

11^{3/4}"x11^{3/4}" - 30x30 cm
(Mosaic 2"x2")



SHORE CREST OBLIK MOSAIC

11^{3/4}"x11^{3/4}" - 30x30 cm
(Mosaic 6"x6")



SHORE SAND OBLIK MOSAIC

11^{3/4}"x11^{3/4}" - 30x30 cm
(Mosaic 6"x6")



SHORE MARINE OBLIK MOSAIC

11^{3/4}"x11^{3/4}" - 30x30 cm
(Mosaic 6"x6")

MOOD



SHORE CREST CUBIK MOSAIC

9"x9" - 23x23 cm
(Mosaic 4.4"x4.4")



SHORE SAND CUBIK MOSAIC

9"x9" - 23x23 cm
(Mosaic 4.4"x4.4")



SHORE MARINE CUBIK MOSAIC


9"x9" - 23x23 cm
(Mosaic 4.4"x4.4")

COORDINATING TRIMS



Bullnose

3"x24" - 7.2x60 cm



Cove base

6"x12" - 15x30 cm - ∇ 8.5mm

Be sure to bring this to your local tile dealer or distributor as you discuss your design.

COLORED BODY PORCELAIN TILE



Compliant with standards ANSI A137.1-2012

SIZE - THICKNESS

11 3/4" x 23 5/8" - 30 x 60 cm
23 5/8" x 47 1/4" - 60 x 120 cm ∇ 9 mm FINISH MATTE



MODERATE VARIATION

While the colors and/or texture present on a single piece of tile will be indicative of the colors and/or texture to be expected on the other tiles, the amount of colors and/or texture on each piece may vary significantly. It is recommended that the range be viewed before selection.

FIELD TILES - Available in all colors

Commercial size (in)	Nominal size (in)	Thickness (mm)	Finish	Rectified Edge
12" x 24"	11 3/4" x 23 5/8"	9 mm	Matte	-
24" x 48"	23 5/8" x 47 1/4"	9 mm	Matte	Yes

MOSAICS AND COORDINATING TRIMS - Available in all colors

Commercial size (in)	Nominal size (in)	Thickness (mm)	Finish
Mosaic 2" x 2"	11 3/4" x 11 3/4"	9 mm	Matte
Oblik Mosaic 6" x 6"	11 3/4" x 11 3/4"	9 mm	Matte
Cubik Mosaic 4.4" x 4.4"	9" x 9"	9 mm	Matte
Bullnose 3" x 24"	2 7/8" x 23 5/8"	9 mm	Matte
Cove Base 6" x 12"	5 7/8" x 11 3/4"	8.5 mm (*)	Matte

Please refer to caliber chart for work sizes. Close joints are not recommended.

(*) Cove Base thickness is 7mm on flat part.

PERFORMANCE & FEATURES

	PROPERTY	ASTM TEST METHOD	Porcelain Tile Specification				
			Calibrated		Rectified		
			Minimum	Maximum	Minimum	Maximum	
REGULARITY CHARACTERISTICS	Nominal Size	ASTM C499	-3.00%	3.00%	-3.00%	2.00%	Compliant
	Caliber Range (Variation from average facial dimension of sample)		-0.50% or -0.08 in (-2.0 mm) (*)	0.50% or 0.08 in (2.0 mm) (*)	-0.25% or -0.03 in (-0.8 mm) (*)	0.25% or 0.03 in (0.8 mm) (*)	Compliant
	Thickness ⁽¹⁾		N/A	Range: 0.40 in (1.02 mm)	N/A	Range: 0.40 in (1.02 mm)	Compliant
	Wedging	ASTM C502	-0.50% or -0.08 in (-2.0 mm) (*)	0.50% or 0.08 in (2.0 mm) (*)	-0.25% or -0.03 in (-0.8 mm) (*)	0.25% or 0.03 in (0.8 mm) (*)	Compliant
	Warpage Edge	ASTM C485	-0.75% or -0.09 in (-2.3 mm) (*)	0.75% or 0.09 in (2.3 mm) (*)	-0.40% or -0.05 in (-1.3 mm)(2) or -1.8 mm(3) (*)	0.40% or 0.05 in (1.3 mm)(2) or 1.8 mm(3) (*)	Compliant
Warpage Diagonal	-0.50% or -0.08 in (-2.0 mm) (*)		0.50% or 0.08 in (2.0 mm) (*)	-0.40% or -0.07 in (-1.8 mm) (*)	0.40% or 0.07 in (1.8 mm) (*)	Compliant	
All Porcelain Tiles							
STRUCTURAL CHARACTERISTICS	Water Absorption	ASTM C373	≤ 0.5%			≤ 0.5%	
BULK MECHANICAL CHARACTERISTICS	Breaking Strength	ASTM C648	Average ≥ 250 lbf. (1.11 kN) Individual ≥ 225 lbf. (1.00 kN)			≥ 350 lbf. avg	
PHYSICAL PROPERTIES	Bond Strength	ASTM C482	≥ 50 psi (0.34 Mpa)			≥ 100 psi	
THERMAL AND IGROMETRIC CHARACTERISTICS	Resistance to Freeze/Thaw Cycling	ASTM C1026	As Reported			Resistant	
CHEMICAL CHARACTERISTICS	Chemical Resistance	ASTM C650	As Reported			Unaffected	
	Stain Resistance	ASTM C1378	As Reported			Unaffected	
SAFETY CHARACTERISTICS	Dynamic coefficient of friction	DCOF	Requires a minimum value of 0.42 for commercial areas that are likely to be wet			> 0.42 Wet	

(*) Whichever is less

(1) May not apply to textured surfaces or tiles with uneven back patterns.

(2) Whichever is less, for tiles up to 24"x24" (610 mm x 610 mm).

(3) Applies to tiles larger than 24"x24" (610 mm x 610 mm).

The Health Product Declaration® logo is a registered trademark of HPD Collaborative.

